

RUBBERPRIME ASP

TECHNICAL DATA SHEET

PRODUCT DESCRIPTION

RUBBERPRIME ASP is a single component, water dispersion of a polymer with film-forming and cross-linking effects. Its particular monomeric composition allows to obtain a film with fairly elastic properties and high surface hardness. RUBBERPRIME ASP is a fluid latex with self-levelling characteristics; Thanks to this feature it can be used alone for substrate applications. **RUBBERPRIME ASP** is recommended for use under SPEC-TRARUBBER as a primer for bitumen substrates.

RUBBERPRIME ASP SPECIFICATION

Appearance	Milky White Liquid
Solid Content	28 - 32%
Density 25°C gm/cc.	7.5 - 9.0 (± 0.02)
Solids Content	± 5°C

APPLICATIONS

- **RUBBERPRIME ASP** is used as is, as a single-component primer.
- **RUBBERPRIME ASP** is suitable for all adsorbent substrates, in particular for the problematic ones (e.g. micro-cellular concrete, adsorbent brick, clay solid bricks and ruined walls); it is able to reinforce the substrate and to improve the anchorage of subsequent applications.
- **RUBBERPRIME ASP** is not indicated for smooth and non-absorbent surfaces (e.g. metal, plastic, glass).

After complete drying, the film obtained has a glossy finish and a non-sticky surface. Drying times depend on humidity, temperature and thickness of the film.

STORAGE & STABILITY

RUBBERPRIME ASP should be stored in sealed containers in a cool environment, preferably above 5°C and below 30°C. Under these conditions, the product has a storage life of 6 months from date of delivery.

SAFETY AND HANDLING

- Although **RUBBERPRIME ASP** is considered practically non-toxic, the usual precautions for working with chemicals should be observed when handling the product.
- For further details, see Material Safety Data Sheet for the usual precautions (available in detail) to be followed when handling and applying isocyanates.
- The information contained in this bulletin is to the best of our knowledge true and correct but any recommendations or suggestions, which may be made, are without guarantee since the conditions of use are beyond our control. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing patents covering any material or its use.
- In accordance with ISO 9001 and the Occupational Health and Safety Act (Act 85 of 1993), herewith Product and Safety Data Sheet.



Safety Rubber Flooring

www.playsafe.africa

RUBBERPRIME ASP

TECHNICAL DATA SHEET

OTHER INFORMATION

The information contained in this data sheet is to the best of our knowledge true and accurate but any recommendations or suggestions, which may be made, are without guarantee, since the conditions of use are beyond our control. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing patents covering any material or its use.

Date issued: 01/05/2020

Revision No.: 0

PlaySafe is a brand of

**SEAMLESS
FLOORING
SYSTEMS**

Seamless Flooring Systems
13 Blomvlei Road
Nerissa Estate, 7780
Cape Town

Tel: 0861 782 789
HQ: 021 762 8617
info@seamlessflooring.co.za
www.seamlessflooring.co.za

1/2021