

### PRODUCT DESCRIPTION

Spectralinfill is produced from granulating recycled SBR rubber which is processed, classified and graded to meet internationally required infill standards. Using a licenced and patented colouring technique, each granule is fully encapsulated in a UV stable and colour-fast pigmented polyurethane.

### APPLICATION

Spectralinfill is pre-coloured SBR rubber granules used as infill for artificial turf sport pitches.

### TECHNICAL DATA

<b>Colours</b>	2 Colours (Green & Brown). Other colours available on request.
<b>Basic material</b>	Processed and graded recycled SBR rubber.
<b>Moisture residue</b>	≤ 0.2%
<b>Hardness</b>	55/60 Shore A.
<b>Coating</b>	UV stable Pigmented Aliphatic Polyurethane coating.
<b>Standard grain size</b>	0.8 – 2.5mm SBR rubber (FIFA Specification).
<b>Packaging unit</b>	25kg bags, stacked on pallets. Upon request, bulk bags of 1000kg. Minimum order per colour – 1000 kg. Export orders packaged as per international guidelines.
<b>Storage</b>	Store in a cool, dry and dark place.
<b>Safety</b>	Read Material Safety Data Sheet.

### SPECIFICATIONS

Particle Sizes	Pack Size	Colours	Rubber Types
0.8 - 2.5mm	25kg Bag	Green / Brown	SBR

#### Disclaimer

The above information is derived from periodic tests taken on actual product from the manufacturing process. Some variances in specifications and raw surface appearances are possible due to the use of recycled materials and our manufacturing tolerances. In practice, the difference in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The recommendation relating to the application and end use of Seamless Flooring Systems' products, are given in good faith, based on Seamless Floor Systems' current knowledge and experience of the product when properly stored, handled and applied under normal conditions in accordance with Seamless Flooring Systems' recommendations. The user of the product must test the product's suitability for intended application and purpose. All orders are accepted subject to our current Terms and Conditions of Sales and delivery. Users must refer to the most recent issue of the Technical Data Sheet for the product concerned, copies of which will be supplied on request.